DOE/ER-0046/7 ~~FRW~~ JLS 5-7-82

Damage Analysis and Fundamental Studies

Quarterly Progress Report
July-Sept 1981

November 1981

U.S. Department of Energy
Assistant Secretary for Energy Technology
Office of Fusion Energy
Washington, DC 20545

CONTENTS

Page

Foreword iii

Figures xii

Tables xviii

CHAPTER 1: IRRADIATION TEST FACILITIES

1. RTNS-II Irradiations and Operations (LLNL) 3

Irradiations were performed on three primary experiments involving Nb, Ti, V, Cu, and mica, and on three secondary ("piggyback") experiments. No major unscheduled outages occurred. A 50 em target was operated at 5000 rpm and high vacuum for 250 hours with no problems encountered.

CHAPTER 2: DOSIMETRY AND DAMAGE PARAMETERS

1. Fission Reactor Dosimetry (ANL) 8

Fluence and damage maps are presented for the EBR-II-X287 experiment. Dosimeters have been provided for several new experiments in HFIR.

2. Characterization of Spallation Neutron Sources (ANL) 17

The Radiation Effects Facility (REF) of the Intense Pulsed Neutron Source (IPNS) became operational in July 1981. Fluence and damage parameters are given for the vertical thimble (VT2) and rabbit irradiation tubes.

3. Heliun Production in ORR MFE 4A Nickel (RIES) 24

A series of analyses has been performed on om of the nickel dosimetry wires removed from the ORR MFE-4A experiment.

CONTENTS (Cont'd)

Page

4. Heliun Generation Cross Sections for 14.8 MeV Neutrons (RIES) 28

The total heliwn generation cross sections have been measured for V, Fe, Ni, Cu, Zr, Nb, Mo, Au and the separated isotopes of Fe, Ni, Cu, and Mo irradiated in RTNS-II. The results are presented along with the previous cross-section measurements made as part of two RTNS-I experiments.

5. Helium Generation Cross Sections for Be(d,n) Neutrons (RIES) 34

Helium analyses have been completed for the Fe, Ni, and Cu isotopes irradiated in the Be(d,n) neutron field, and average integral cross sections huve been determined for all of the Be(d,n)-irradiated materials analyzed to date.

6. Measurements of the $^{27}Al(n,2n)^{26}Al$ Cross Section (ANL) 39

A new technique, AMS (accelerator mass spectrometry), was used to measure the (n,2n) cross section in aluminum. The experimentally measured cross section was found to be approximately one half the theoretically calculated cross section presently being used in neutron damage calculations.

7. Nuclear Data Applications in Radiation Damage Studies (HEDL) 50

Vanadium was added to the nuclear cross section library associated with the transmutation code REAC.

The damage energy cross sections and helium production from ENDF/B-V for 25 materials were processed with the NJOY code.

CONTENTS (Cont'd)

8. Reflection of Low Energy Helium Atoms From Tungsten Surfaces (ORNL) 53

The computer program MARLOWE (Version 11.5) has been used to simulate the reflection of 8 eV to 1.5 keV heliwn atoms from monocrystalline, polycrystalline, and amorphous tungsten targets. Comparisons of calculated and measured ion ranges indicate that the electronic stopping cross section of low energy heliwn atoms in tungsten is significantly greater than the traditional LSS value. The reflection coefficients calculated for the <001> surface are in fair agreement with experiment.

9. Radiation Damage Studies (U. of Wisconsin) 66

Range and damage calculations with the new Monte Carlo computer program HERAD shows improved agreement with recent range and damage experimental data. The effect of voids developed during irradiation is included. A parameter study indicates that the electronic stopping cross section of low energy He in Ni is significantly lower than the traditional LSS value.

CHAPTER 3: FUNDAMENTAL MECHANICAL BEHAVIOR

1. Environmental Effects on Fracture of Fusion Reactor Materials (PNL) 81

The known stress corrosion and corrosion fatigue fracture processes in austenitic and ferritic steels are reviewed with an emphasis on aqueous and liquid metal environments. Possible effects of irradiation are discussed and precautions are given for the use of austenitic and ferritic stainless steels in fusion reactor environments. Finally, an approach to modeling the environmental effect on the local fracture toughness at the tip of a crack is given.

CONTENTS (Cont'd)

CHAPTER 4: CORRELATION METHODOLOGY

1. Fusion Swelling Predictions From a Model-Based Fission-Fusion-Fission Interpolation (UCSB) 97

The helium/dpa (He/dpa) ratio in stainless steel under fusion conditions will be about 30 times greater than in EBR-II and about 7 times less than in HFIR. A rate theory model that explicitly considers some potential He/dpa ratio effects has been calibrated using data from both EBR-11 and HFIR. Application of the model to fusion conditions indicates that simple extrapolations of swelling data from either EBR-11 or HFIR may not be valid.

2. Helium Bubble Formation and Swelling in Metals (U. of Wisconsin, HEOL) 114

The effect of continuous production of helim on swelling is analyzed using an improved equation of state for gaseous helim that incorporates both a gas-kinetic as well as a static pressure for densely packed helim. At high temperatures, bubbles grow by thermal vacancy emission at dislocations and their absorption at cavities. For high He/dpa ratios, bubbles remain overpressurized, and swelling is less than if equilibrium is assmed. At low temperatures, swelling or void growth driven by a modest bias is always larger than bubble swelling, and helim has no effect on the swelling rate.

3. The Radiation-Induced Evolution of AISI 316 (DO-Heat) in HFIR and EBR-II (HEDL) 127

Examination of a HFIR-irradiated specimen at 42 dpa shows that the dislocation and phase evolution are consistent with that of comparable EBR-II irradiated material but that the void densities are higher. Microchemical analyses show that evolution is in progress

Page

at 42 dpa and it is expected that the swelling rate will increase at higher fluence.

4. Miqration and Trapping of Heliun by Cavities and Dislocations in Dual Ion Irradiated Stainless Steels (W-R&D) 142

The results of dual ion experiments suggest that approximately 99 percent of the helim is in visible cavities near the peak swelling temperature. Numerical calculations of helim partitioning based on cavity and dislocation sink strengths for vacancies are shown to over-estimate the number of gas atoms associated with dislocations, and to reduce the maximum possible equilibrium bubble size by a factor of two.

5. Bubble Growth Kinetics Associated With Irradiated and Postirradiation Annealed Metals (U. of Virginia) 155

During in-situ observations of the irradiation of chemical vapor deposited Ni films with He ions, it was found that the growth rate of bubbles on the grain boundary increased up to 4.5 times that of bubbles growing in the grain interior. Neighboring bubbles on a grain boundary were dynamically seen shrinking and growing in volume exchange patterns when the He-irradiated Ni was annealed. The annealing of He irradiated 316 stainless steel specimens showed that bubbles grew in underpressurized states as well as in overpressurized states; the overpressurized bubbles were found to grow more rapidly than underpressurized bubbles.

6. Single- and Dual-Ion Irradiations of Ferritic Alloys and Type 316 Stainless Steel (ANL) 167

Ferritic alloys were single- and dual-ion irradiated to isolate the effects of nickel additions and helium; 316 SS was irradiated for studies of helim injection schedule and prior thermomechanical treatment. Specimens have not yet been analyzed.

CONTENTS (Cont'd)

Page

7. Further Examination of Swelling of "Pure" AISI 316 Irradiated in DRR (HEDL), 172

Examination of additional specimens of Fe-17Cr-16.7Ni-2.5Mo corroborate the previously reported result that cold working of this "pure" 316 alloy has no influence on suppressing void formation.

Density change and aging studies indicate that swelling exists in the form of unresolvable voids in specimens of this alloy preinjected with 40 appm heliwn.

8. The Effect of Applied Stress on Precipitate Stability in Irradiated AISI 316 (MIT, HEDL) 180

A particular state of applied stress may either stabilize, destabilize, or have no effect on a particular phase, depending on the transformation strain.

Shear stresses can alter precipitation as effectively as hydrostatic stresses. It appears, however, that the acceleration of swelling of AISI 316 by applied stress at high temperature is accomplished by the hydrostatic and not the deviatoric components.

9. Measurement and Calculation of Solid Transmutants Formed in AISI 316 (HEDL) 198

A reassessment of the calculation of two transmutation products produced in HFIR irradiations of AISI 316 has shown that the inclusion of all competing reactions leads to changes in the predicted concentrations. The peak vanadium level is reduced somewhat from what was reported earlier, but not enough to dismiss it as a potential determinant of alloy behavior. The

Page

copper level has been increased substantially, but not enough to influence the swelling of AISI 316.

10. A Model for the Evolution of Network Dislocation Density in Irradiated Metals (U. of Wisconsin, HEDL) 210

A model has been developed to explain the relative insensitivity of network dislocation density in irmdiated metals at high fluence to starting microstructure, temperature, stress and displacement rate. The model also explains how the rate of approach to saturation can be sensitive to flux and temperature while the saturation level itself is not dependent on temperature.

11. The Microstructural Origins of Yield Strength Changes in AISI 316 During Fission or Fusion Irradiation (HEDL) 220

The changes in yield strength of AISI 316 irradiated in fast reactors have been successfully modeled in tens of concurrent changes in microstructural components. Extrapolation to anticipated fusion behavior based on microstructural cmparisons leads to the conclusion that the primary influence of transmutational differences in non-pulsed environments is to alter the tmnsient behavior and not the saturation level of yield strength.

12. Canpositional Dependence of Radiation-Induced Change in Dimensional and Physical Properties of Fe-Cr-Ni Austenitic Alloys (U. of Wisconsin, HEDL) 234

Nickel segregates to void embryos in these alloys, increasing the nickel level at their surfaces, and leading to changes in their interstitia2 capture efficiency. This leads to changes in the void nucleation rate and the duration of the transient regime of swelling.