



Damage Analysis and Fundamental Studies

Quarterly Progress Report
January-March 1983

May 1983

U.S. Department of Energy
Office of Energy Research
Office of Fusion Energy
Washington, DC 20545

CONTENTS

	<u>Page</u>
Foreword	iii
Figures	x
Tables	xvii
 CHAPTER 1: <u>IRRADIATION TEST FACILITIES</u>	
1. <u>RTNS-II Irradiations and Operations (LLNL)</u>	3
<i>Irradiations were performed for 21 different experimenters during this quarter. The second U.S.-Japan Steering Committee meeting was held February 9-11, 1983. Work has begun on the preparation of the right machine for initial operation.</i>	
2. <u>Light Ion Accelerator Facility to Study the Effects of Interstitial Helium and Hydrogen Atoms on Microstructural Evolution in Self-Ion Irradiated Nickel (U. of Wisconsin)</u>	7
<i>Initial experiments have been completed to characterize the phase space properties of the beam as it leaves the accelerator. Irradiations of annealed nickel foils with He⁺ and H⁺ beams at 700 keV were completed to determine maximum operating parameters of the system.</i>	
3. <u>Intense Titanium Ion Beam for Radiation Damage Studies (U. of Wisconsin)</u>	11
<i>A beam of TiH⁻ ions suitable for heavy-ion irradiation studies utilizing a tandem accelerator has been developed and characterized. Beam currents and emittances are presented with estimated operating lifetimes of sputter cathodes.</i>	

CONTENTS (Cont'd)

	<u>Page</u>
CHAPTER 2: <u>DOSIMETRY AND DAMAGE PARAMETERS</u>	
1. <u>Fission Reactor Dosimetry - HFIR - CTR31, 32, 34, and 35</u> <u>(ANL)</u>	17
<i>Measurements of neutron fluxes and energy spectra for four irradiations in HFIR, designated CTR31, 32, 34, and 35, agree quite well. The status of all other dosimetry experiments is summarized.</i>	
2. <u>Measurement of the $^{27}\text{Al}(n,2n)^{26}\text{Al}$ Cross Section Near</u> <u>Threshold (ANL)</u>	27
<i>It may be possible to measure plasma ion temperatures by comparing $^{27}\text{Al}(n,2n)^{26}\text{Al}$ reaction rates with the $\text{Al}(n,p)$ and $\text{Al}(n,\alpha)$ reaction rates that vary much more slowly near 14 MeV.</i>	
3. <u>Helium Production Cross Sections for 14.8-MeV Neutrons (RIES)</u>	38
<i>Total helium production cross sections have been determined at $E_n = 14.8$ MeV for C (graphite), Y, Ag, and Ta irradiated in RTNS-II, and for ^6Li, ^7Li, ^{10}B, and ^{11}B irradiated in RTNS-I.</i>	
4. <u>The Effects of Collision Cascade Properties on the Diffusion</u> <u>of Point Defects in Irradiated Materials (UCLA)</u>	44
<i>Vacancy and interstitial cascades are modeled as concentric spheres in a Monte-Carlo solution to the point defect diffusion problem. It is shown that large cascades typical of fusion spectra may lead to a small fluctuation in the average concentration of point defects. An assessment of the validity of rate theory is given.</i>	

CONTENTS (Cont'd)

	<u>Page</u>
CHAPTER 3: <u>REDUCED ACTIVATION MATERIALS</u>	63
1. <u>Activation of Components of a Fusion Alloy (HEDL)</u> <i>The activation of 27 elements at the STARFIRE first wall position for a 2-year irradiation period and for various cooling times was calculated. Comparing the results to present NRC regulations on waste disposal indicates that N, Ni, Cu, Nb, and Mo additions to steels might face restrictions.</i>	
CHAPTER 4: <u>FUNDAMENTAL MECHANICAL BEHAVIOR</u>	
1. <u>Grain Boundary Chemistry, Hydrogen Embrittlement and Stress Corrosion Behavior of HT9 (PNL)</u>	77
<i>The grain boundary phosphorus and sulfur concentrations of HT9 were found to depend on heat treatment in a manner consistent with other ferritic steels. Straining electrode tests at cathodic and anodic test potentials revealed that HT9 is sensitive to hydrogen embrittlement but not stress corrosion at 25°C in an acidic electrolyte. The reduction of area was 13% at cathodic test potentials and 60% in air and at anodic test potentials. This decrease in reduction of area was accompanied by an increase in quasi-cleavage and intergranular fracture.</i>	
2. <u>Radiation-Induced Segregation of Phosphorus in Fusion Reactor Materials (PNL)</u>	103
<i>The magnitude of phosphorus segregation in ferritics is much less than in stainless steel. Sputtering places an inherent limitation on the heavy ion irradiation technique for the study of surface segregation of impurity elements.</i>	

CONTENTS (Cont'd)

	<u>Page</u>
CHAPTER 5: <u>CORRELATION METHODOLOGY</u>	
1. <u>The Development of Model-Based Swelling Equations for Fusion Design Applications (UCSB)</u>	115
<i>The predictions of a rate theory swelling model, calibrated to fission reactor data, have been used to develop preliminary design equations for the swelling of 20% cold-worked AISI 316 stainless steel in a fusion reactor first wall. These equations complement two empirical equations developed elsewhere.</i>	
2. <u>Bias in Ferritic and Austenitic Alloys (U. of Wisconsin)</u>	126
<i>The hypothesis is advanced that the difference in the swelling behavior of austenitic and ferritic alloys originates from the difference in the net bias. Equations are given for the bias factors of voids and dislocations for both interstitial and vacancy capture. The net bias is found to be smaller by about a factor of four in ferritic steels as compared to austenitic steels. With the value obtained for austenitic steels, an upper swelling rate of $\sim 1.4\%/dpa$ is expected. This compares favorably with the empirical value of $\sim 1\%/dpa$.</i>	
3. <u>Effect of Bubble Radius on the Equation of State for Gases (U. of Wisconsin-Madison)</u>	148
<i>The gas pressure derived from a thermodynamic equation of state is only equal to the gas-kinetic pressure exerted on a surface whose radius of curvature is very large compared with the radius of the gas molecules or atoms. Curvature corrections show that the gas-kinetic pressure in small bubbles can be significantly larger than the pressure obtained from the thermodynamic equation of state.</i>	

CONTENTS (Cont'd)

	<u>Page</u>
4. <u>Contribution of Vacancies to the Equation of State of Solid Helium (U. of Wisconsin)</u>	164
<i>It is found that vacancies make only a minor contribution to the equation of state at the high temperatures of interest to radiation damage and blistering applications.</i>	
5. <u>Grain Boundary Helium Deposition in Nickel-Bearing Alloys Irradiated in Mixed Spectrum Reactors (U. of Missouri-Rolla)</u>	170
<i>A general derivation was performed to determine the effect of nickel segregation on the helium deposition rate at the grain boundary in nickel-bearing alloys under irradiation in mixed spectrum nuclear reactors.</i>	
6. <u>A Computerized "Reference Manual" for Literature on Helium Effects (UCLA, ORNL)</u>	180
<i>A summary is given of a computerized "Reference Manual" for all available literature on helium effects on solids. The report is divided into 12 chapters, each dealing with research on a particular area. The entries to publications are given alphabetically and chronologically within each year.</i>	
7. <u>Cross-Section Technique for Ion-Irradiated AISI 316 SS (U. of Wisconsin)</u>	186
<i>A cross-section technique involving nickel plating on a 316 SS substrate has been demonstrated for 14-MeV $^{58}\text{Ni}^{3+}$ irradiated 316 SS. Unlike a previous technique for cross-sectioning 316 SS, this method does not rely on a high temperature diffusion bond between the nickel and the 316 SS.</i>	