



---

# Damage Analysis and Fundamental Studies

Quarterly Progress Report  
July-September 1984

---

**November 1984**

---

**U.S. Department of Energy**  
Office of Energy Research  
Office of Fusion Energy  
Washington, DC 20545

## CONTENTS

	<u>Page</u>
Foreword	iii
CHAPTER 1: IRRADIATION TEST FACILITIES	1
1. <u>RTNS-II Irradiations and Operations (LLNL)</u>	2
<p>Nine different experiments were irradiated this quarter, ranging from a dual-temperature furnace irradiation (completed) to a cryogenic irradiation (in progress), both of which are studies of radiation effects in metals and alloys. A new materials testing laboratory is now in use.</p>	
CHAPTER 2: DOSIMETRY AND DAMAGE PARAMETERS	4
1. <u>Fission Reactor Dosimetry - HFIR - CTR40-45 (ANL)</u>	5
<p>Dosimetry measurements and damage calculations are reported for the CTR40-45 irradiations in HFIR. Neutron fluences are about <math>5 \times 10^{22}</math> n/cm<sup>2</sup> for 40, 41, 44, and 45 and about <math>9 \times 10^{22}</math> n/cm<sup>2</sup> for 42 and 43.</p>	
2. <u>Helium Generation Measurements for Iron from HFIR (RI)</u>	9
<p>Helium generation measurements on iron irradiated in HFIR agree with ANL predictions based on ENDFIB-V cross sections to within 7%.</p>	
3. <u>Displacement and Helium Generation Rates in the Materials Open Test Assembly of the Fast Flux Test Facility (HEDL)</u>	12
<p>The axial distribution of dp/asec and hpa/sec for the FFTF MOTA were calculated for the following elements: Al, Si, Ti, V, Cr, Mn, Fe, Ni, Cu, Nb, and Mo.</p>	
CHAPTER 3: REDUCED ACTIVATION MATERIALS	23
1. <u>Reduced Activation Guidelines in Perspective (HEDL)</u>	24
<p>Current estimates of composition limits to qualify materials for shallow landburial should be used only as guidelines identifying potential problem elements.</p>	
2. <u>Swelling of Fe-Cr-Mn Ternary Alloys in FFTF (HEDL)</u>	31
<p>The neutron-induced swelling of Fe-Cr-Mn ternary alloys at 15 dpa and approximately 520°C is much less sensitive to composition than are Fe-Cr-Ni alloys.</p>	
3. <u>Compositional Dependence of Ion-Induced Swelling in Fe-Cr-Mn Alloys (ORNL and HEDL)</u>	34
<p>A series of simple Fe-Cr-Mn alloys has been prepared and will be irradiated with iron ions in order to determine the influence of alloy composition on void swelling.</p>	
CHAPTER 4: FUNDAMENTAL MECHANICAL BEHAVIOR	36
1. <u>shear Punch and Ball Microhardness Measurements of 14-MeV Neutron Irradiation Hardening in Five Metals (UCSB)</u>	37
<p>Five metals, including Ni, Ni-5 Si, Fe, PCA, and MFE 316 stainless steel, were irradiated at room temperature in RTNS-II to neutron fluences in the range <math>6 \times 10^{16}</math> to <math>6 \times 10^{17}</math> n/cm<sup>2</sup>. Ball microhardness and shear punch measurements of mechanical properties are shown to be complementary and in good agreement.</p>	

	<u>Page</u>
2. <u>Radiation-Induced Segregation of Phosphorous in Fusion Reactor Materials (PNL)</u>	45
Very low dose ion bombardment of iron-phosphorus and nickel-phosphorus alloys confirms that radiation-induced phosphorus segregation is much lower in these materials than in 316 stainless steel.	
CHAPTER 5: CORRELATION METHODOLOGY	48
1. <u>Reirradiation of HFIR Specimens in FFTF (HEDL and ORNL)</u>	49
Specimens of AISI 316 and PCA, previously irradiated in HFIR to doses of 10-44 dpa and up to 3600 appm helium, have been placed in FFTF for an additional 30-60 dpa. Between irradiations, immersion density measurements were made.	
2. <u>Influence of Titanium on the Neutron-Induced Swelling of Austenitic Alloys (HEDL)</u>	52
Addition of titanium to variants of AISI 316 stainless steel does not significantly alter the eventual swelling behavior during neutron irradiation. In general, titanium additions only temporarily suppress the onset of swelling.	
3. <u>Compositional Micro-Oscillations in Ion-Bombarded Fe-35.0Ni-7.0Cr (HEOL and GE)</u>	56
The compositional micro-oscillations observed in neutron-irradiated Fe-35.5Ni-7.5Cr at 593°C and 38 dpa have also been found in Fe-35.0Ni-7.0Cr irradiated with nickel ions to 117 dpa at 625°C.	
4. <u>Influence of Cold Work on the Neutron-Induced Swelling of Simple Fe-Ni-Cr Ternary Alloys (HEDL)</u>	62
The swelling of simple Fe-Ni-Cr ternary alloys in EBR-II appears to be sensitive to both irradiation temperature and cold work, suggesting that cold work influences the tendency of Fe-Ni-Cr alloys to order.	
5. <u>Swelling of Neutron-Irradiated 85Ni-15Cr at 400-650°C (HEDL)</u>	66
The swelling of the binary alloy 85Ni-15Cr under neutron irradiation is quite different from that of either Fe-Ni-Cr alloys or pure nickel, suggesting that the tendency for long-range order in nichrome alloys is significant.	
6. <u>Vacancy Cluster Evolution in Metals Under Irradiation (U.WI.)</u>	74
A stochastic treatment of vacancy cluster formation in irradiated metals is formulated in terms of a Fokker-Planck equation, the nonlinearity of which provides an important feedback for the evolution of the bias. A peaked distribution of stable voids is distinguished from a distribution of small unstable voids. The predicted values of void number density are in close agreement with measured values.	
7. <u>The Effect of Helium Clustering on Its Transport to Grain Boundaries (UCLA and KFK)</u>	90
A rate theory model is used to develop a solution to the problem of the rate of helium absorption at grain boundaries in an irradiated material. Both homogeneous and heterogeneous nucleation of helium traps are included in the analysis of helium transport. Matrix clustering is an effective impediment to the transport of helium to grain boundaries only for a short irradiation time. Precipitate densities below approximately $10^{13} \text{ cm}^{-3}$ may be ineffective helium traps. The effect of displacement damage on gas re-solution is discussed, and shown to have a particular significance in the determination of the average cavity density.	
8. <u>The Influence of Silicon on Void Nucleation in Irradiated Alloys (U. of MO-Rolla and HEDL)</u>	114
The addition of silicon to pure nickel, Ni-Cr alloys, and Fe-Ni-Cr alloys raises the diffusivity of each of the alloy components. The resultant increase in the effective vacancy diffusion coefficient causes large reductions in the nucleation rate of voids during irradiation.	

CONTENTS (Continued)

9.	<u>Dual Ion Irradiation: Impact of the Conflicting Roles of Helium on Void Nucleation (U. of MO-Rolla and HEDL)</u>	120
	Dual-ion irradiation may not simulate well the helium effects on microstructure to be expected in a fusion device. This is because of the synergistic effects of the injected interstitials, and the unpaired interstitials that result from helium-vacancy trapping.	
CHAPTER 6: FUNDAMENTAL STUDIES OF SPECIAL PURPOSE MATERIALS		131
1.	<u>Swelling of Commercial Copper Alloys and NiBe Irradiated in FFTF (HEOL)</u>	132
	The swelling of various copper alloys irradiated to approximately 16 dpa in the MOTA 1B experiment ranged from -0.66% to 16.6%, the latter for a Cu-0.1% Ag alloy.	
2.	<u>Tensile Property Changes of Commercial Copper Alloys Neutron Irradiated at 450°C (HEDL)</u>	135
	Changes in tensile properties of many of the copper alloys irradiated in FFTF-MOTA at 450°C to approximately 16 dpa are dominated by thermal effects.	
3.	<u>Conductivity Changes in Neutron-Irradiated Commercial Copper Alloys at Approximately 450°C (HEDL)</u>	138
	FFTF-MOTA irradiation of copper alloys at 450°C to approximately 16 dpa resulted in an increase in electrical conductivity of Be-containing alloys and a decrease in the others; the change appears to correlate with the unirradiated conductivity.	
4.	<u>Swelling of Beryllium (U. of WI-Madison and TRW)</u>	140
	A comparison of the displacement rate and the helium production rate produced in beryllium by 14-MeV neutrons shows that the helium production rate is the predominant mechanism for swelling. A simple model is developed which reproduces the data for swelling produced in fission reactors.	
CHAPTER 7: FUNDAMENTAL STUDIES SUPPORTED BY OTHER AGENCIES		146
1.	<u>Basic Radiation Effects Research at Oak Ridge National Laboratory (ORNL)</u>	147
A.	<u>Experimental Determination of the Critical Cavity Radius in Fe-10% Cr for Ion Irradiation (ORNL)</u>	148
	A critical cavity radius of 25 nm and a bias of 0.2 was deduced from an irradiation at 850 K with 4 MeV Fe <sup>++</sup> ions. Estimates of other fundamental parameters are given.	
B.	<u>Evidence for a Mechanism of Swelling Variation with Composition in Irradiated Fe-Cr-Ni Alloys (ORNL)</u>	157
	The mechanism for the swelling resistance of Fe-35Ni-15Cr relative to that of Fe-15Ni-15Cr was investigated using both dual ion and helium-injection-plus-single-ion (Ni) irradiation. A much larger critical cavity radius was deduced for the high nickel alloy. It is suggested that this correlates with increased resistance in the high nickel alloy to interstitial absorption at interstitial-typedislocation loops.	
3.	<u>An Approximate Analytical Calculation of Precipitate Dissolution Rate Using a Slowing Down-Diffusion Theory for Charged Particles (UCLA)</u>	171
	Dissolution parameters which control the stability of precipitates show that the concept of a modified "escape zone" for precipitate atoms from its surface is a valid representation of the phenomenon. It is shown that, for large precipitates, the dissolution rate is approximately proportional to the incident ion energy and inversely proportional to the precipitate radius.	