



Damage Analysis and Fundamental Studies

Quarterly Progress Report
October-December 1985

February 1986

U.S. Department of Energy
Office of Energy Research
Office of Fusion Energy
Washington, DC 20545
B&R No. AT-15-02-03-04

CONTENTS

	<u>Page</u>
Foreword	
CHAPTER 1: IRRADIATION TEST FACILITIES	
1. <u>RTNS-II IRRADIATIONS AND OPERATIONS (LLNL)</u>	2
<p>Irradiations were performed on nine different experiments during this quarter. The next U.S./Japan Steering Committee meeting will be held February 6 and 7, 1986, at RTNS-II.</p>	
CHAPTER 2: DOSIMETRY AND DAMAGE PARAMETERS	
1. <u>DOSIMETRY AND DAMAGE ANALYSIS FOR THE HAFNIUM FULL-POWER TEST, JP1, AND JP3 EXPERIMENTS IN HFIR (ANL)</u>	5
<p>Results are reported for the full-power hafnium test for one cycle (22 days) in HFIR. Neutron exposure measurements and damage calculations are similar to the low-power spectral runs reported previously. Analysis has also been completed for the JP1 and JP3 experiments in HFIR. These two experiments had an identical exposure history resulting in a fast (>0.1 MeV) neutron fluence of about $3.9 \times 10^{22} \text{n/cm}^2$ producing 32 dpa and 2147 appm helium in 316 stainless steel.</p>	
2. <u>TRANSMUTATIONS IN FUSION TEST FACILITIES (HEDL)</u>	10
<p>Transmutation rates in FFTF, HFIR, STARFIRE, and MARS spectra are compared.</p>	
CHAPTER 3: REDUCED ACTIVATION MATERIALS	
1. <u>PHASE DEVELOPMENT AND SWELLING IN Fe-Mn AND Fe-Cr-Mn ALLOYS DURING NEUTRON IRRADIATION (HEDL)</u>	22
<p>Second phases form in irradiated Mn-containing iron-based steels, especially at low Cr contents, unlike their Ni-containing counterparts.</p>	
2. <u>ACTIVATION CALCULATIONS USING AN EXPANDED NUCLEAR DATA BASE (HEDL)</u>	30
<p>The water cooling of STARFIRE produces a low energy tail in the neutron spectrum that may impact the use of W in reduced activation alloys intended for service to high fluences.</p>	
CHAPTER 4: RADIATION EFFECTS MECHANISMS AND CORRELATIONS	
1. <u>OWR/RTNS-II LOW EXPOSURE SPECTRAL EFFECTS EXPERIMENT (HEDL)</u>	38
<p>The first tensile data from OWR are compared to RTNS-II data at 90°C. The data for solution-annealed 316 stainless steel correlate well with dpa; those for copper do not.</p>	
2. <u>MICROSTRUCTURAL EXAMINATION OF Fe-Cr BINARY FERRITIC ALLOYS FOLLOWING IRRADIATION TO 15 DPA IN FFTF (HEDL)</u>	43
<p>Six Fe-Cr binary alloys (from 3 Cr to 18 Cr) were irradiated in FFTF at 430°C to 15 dpa. Swelling was highest, 0.26 percent, in the Fe-9Cr alloys with a corresponding dislocation network comprising equal parts of $\alpha \langle 100 \rangle$ and $\alpha/2 \langle 111 \rangle$ Burgers vectors. An example of a deformation slip band containing elongated voids was found which indicates that channel fracture may occur in ferritic alloys that contain uniform void swelling.</p>	

3. NUCLEATION OF GRAIN BOUNDARY CAVITIES UNDER THE COMBINED INFLUENCE OF HELIUM AND APPLIED STRESS (U, OF KUWAIT AND U, OF CALIFORNIA-LA) 57
- It is shown through modeling that injecting helium to as low as one part per million can result in grain boundary bubble densities on the order of 10^9cm^{-2} . Such cavity population exceeds typical grain boundary cavity densities associated with creep experiments. Grain boundary bubble densities are shown to reach steady state for injected helium amounts on the order of 10 parts per million.
4. NEUTRON-INDUCED SPINODAL-LIKE DECOMPOSITION OF Fe-Ni AND Fe-Ni-Cr ALLOYS (HEDL) 71
- Several new experiments illuminate the nature of the spinodal-like decomposition that occurs during charged particle or neutron irradiation of alloys in the Invar compositional regime.
5. THE INFLUENCE OF UNCERTAINTIES IN MATERIAL PROPERTIES AND THE EFFECTS OF DIMENSIONAL SCALING ON THE PREDICTION OF FUSION STRUCTURE LIFETIMES (U, OF CALIFORNIA-LP) 77
- The sensitivity of lifetime predictions for fusion reactor blanket structures is investigated by applying the Monte Carlo numerical technique. Irradiation creep rates are shown to be sufficient for relaxation of swelling-induced stresses under most conditions. A lifetime of several hundred dpa is shown to be highly probable for the MARS blanket design.
- CHAPTER 5: FUNDAMENTAL STUDIES OF SPECIAL PURPOSE MATERIALS**
1. SWELLING OF PURE COPPER AND COPPER ALLOYS AFTER HIGH FLUENCE IRRADIATION IN FFTF AT $\sim 450^\circ\text{C}$ (HEDL) 89
- Neutron-induced density change data to 47 and 63 dpa at 450°C fell into two categories--those that exhibit pronounced swelling (often with s-shaped behavior) with dpa level and those that resist the onset of swelling to very large exposures.
2. NEUTRON IRRADIATION OF COPPER AND HIGH-CONDUCTIVITY COPPER ALLOYS IN EBR-II (LANL AND MIT) 94
- The alumina-dispersed copper alloys (Glidcop A1-20 and A1-60) exhibited the greatest resistance to neutron damage (15 dpa at 385°C) among the six materials tested.